



ATTACHED LENS PROJECTORS







DECEMBER 2009

CLASSROOM PROJECTORS

	ENTRY LEVEL		FULL FEATURED		LOW MAINTENANCE	
Note: Photos are not sized to scale.						
MODEL	LC-XBL20 / 25	EIP-2600	LC-XB100 / 200	LC-WB100	LC-XS25 / 30 / 31*	LC-XDP3500
KEY FEATURES	Operates as quiet as 29 dBA; Network monitoring and control	'Seamless' DLP® imaging; 6-segment Brilliant Color color wheel; Full range of inputs, including digital (DVI-I); Filterless design; Long lamp life	7 watt sound system; Compact design and only 6.2 lb; Digital input with DVI-I port; Network monitoring and control	Widescreen, 720p; 7 Watt sound output; Digital input with HDMI port; Only 6.2 lb	Cartridge air filter; Filter and lamp warranties for first year; Digital input with DVI-I port; 7 Watt audio system; XS31: Wired LAN connection	"Dustproof" design with HEPA-like filter (up to 5,000 hours); Anti-smoke filter included; Wired LAN; Easy, side access to lamp and filter
DISPLAY TECHNOLOGY	3LCD	1-chip DLP®	3LCD	3LCD	3LCD	3LCD
PRICE (MSRP)	\$895 / \$995	\$1,195	\$1,295 / \$1,495	\$1,495	\$1,295 / \$1,395 / \$1,495	\$1,995
BRIGHTNESS (ANSI)	2,200 / 2,600 lumens	2,600 lumens	3,000 / 3,500 lumens	2,500 lumens	2,600 / 3,100 / 3,100 lumens	3,500 lumens
NATIVE RESOLUTION	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	WXGA (1280x800)	XGA (1024x768)	XGA (1024x768)
MAX. COMPUTER INPUT	UXGA	UXGA	UXGA	WUXGA	UXGA	UXGA
MAX. VIDEO INPUT	1080i	1080p	1080i	1080i	1080i	1080p
CONTRAST RATIO	500:1	2200:1	500:1	500:1	450:1	500:1
PANEL SIZE	0.55"	0.55"	0.63"	0.59"	0.63"	0.63"
LENS TYPE	1.62-1.92:1	1.64-1.97:1	1.18-1.91:1	1.18-1.91:1	1.72-2.07:1	1.45-1.73:1
FIXED IMAGE OFFSET	Up 35.7%	Up 15.5%	Up 40%	Up 48%	Up 40%	Up 33.3%
KEystone CORRECTION	U/D 30°	U/D 40°	U/D 30°	U/D 30°	U/D 20°	U/D 30°
CLOSED CAPTION	Yes	Yes	Yes	Yes	Yes	Yes
INPUTS	Dsub15 x 2; RCA x 1 MiniStereo x 1; S-Video with included adapter	DVI-I (w/HDCP) x 1; Dsub15 x 1 S-Video x 1; RCA x 1 RCA (audio) x 2; MiniStereo x 1	DVI-I (w/HDCP) x 1; Dsub15 x 1 RCA x 1; S-Video x 1 MiniStereo x 2; RCA (audio) x 2	Dsub15 x 2; HDMI (w/HDCP) x 1 S-Video x 2; RCA x 1; MiniStereo x 2 RCA (audio) x 2	DVI-I (w/HDCP) x 1; Dsub15 x 1 RCA x 1; S-Video x 1 MiniStereo x 2; RCA (audio) x 2	Dsub15 x 1; DVI-I (w/HDCP) x 1 S-Video x 1 or RCA x 1 or RCA x 3 MiniStereo x 1; RCA (audio) x 2
OUTPUTS	Dsub15 x 1; MiniStereo x 1 (by switching inputs)	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1 (by switching inputs)	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1 (by switching inputs)	Dsub15 x 1; MiniStereo x 1 (by switching inputs)
SOUND CONTROL	1 Watt; 1.1" dia. speaker x 1	2 Watt; 1.1" dia. speaker x 1	7 Watt; 1.4" dia. speaker x 1	7 Watt; 1.4" dia. speaker x 1	7 Watt; 1.4" dia. speaker x 1	8 Watt; 2" dia. speaker x 1
NETWORK CONTROL	Wired LAN monitoring and control	—	Wired LAN monitoring and control	Wired LAN monitoring and control	XS31 (only) Wired LAN monitoring and control	Wired LAN monitoring and control
WARRANTY	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)
LAMP LIFE	Up to 3,000 hours	Up to 4,000 hours	Up to 2,500 hours	Up to 2,500 hours	Up to 3,000 hours	Up to 3,000 hours
LAMP PART NUMBER	610 345 2456	AH-62101	610 343 2069	610 343 2069	610 339 8600	23040021
FAN NOISE	As low as 29 dBA	As low as 29 dBA	As low as 29 dBA	As low as 29 dBA	As low as 27.5 dBA	As low as 33 dBA
AIR FILTER	Standard	None	Standard	Standard	Cartridge (up to 3,000 hours)	HEPA-like (up to 5,000 hours)
MAXIMUM PITCH	± 30° U/D	± 9° U/D	± 12° U/D	± 30° U/D	± 20° U/D	Up to 360°
WEIGHT	5.5 lb (2.5 kg)	6.4 lb (2.9 kg)	6.2 lb (2.8 kg)	6.2 lb (2.8 kg)	8.82 lb (4.0 kg)	8.2 lb (3.7 kg)
CEILING MOUNT PN	0173-4341	0173-5014	0173-4338	0173-4338	0173-4327	0173-4142

EIKI INTERNATIONAL, INC.

30251 Esperanza, Rancho Santa Margarita, CA 92688 Tel: 800-242-3454 E-Mail: usa@eiki.com Website: www.eiki.com

ULTRA-PORTABLES					
	ROAD WARRIOR	COST EFFECTIVE	 PORTABLE / INSTALLABLE		
Note: Photos are not sized to scale.					
MODEL	LC-XD25 / LC-XD25U	LC-XB33N	LC-XB42 / 43*	LC-XB42N	LC-WB42N
KEY FEATURES	Our smallest projector; 2,500 lumens, very compact & only 3.6lb; Uniquely small and bright, full-featured LCD	Wireless network monitoring, control and content delivery; Computerless SD slideshow; Lightweight and compact	Only 7.9 lb and 4,500 lumens; Brightest projector in its class; XB43: Wired LAN connection	Wireless network monitoring, control and content delivery; Only 8.2 lb and 4,500 lumens; Computerless SD slideshow	Wireless network monitoring, control and content delivery up to 802.11n; Only 7.9 lb; Computerless USB slideshow; Easy network-free wireless
DISPLAY TECHNOLOGY	3LCD	3LCD	3LCD	3LCD	3LCD
PRICE (MSRP)	\$1,195 / \$1,295	\$2,495	\$2,495 / \$2,745	\$3,395	\$2,995
BRIGHTNESS (ANSI)	2,500 lumens	3,000 lumens	4,500 / 4,500 lumens	4,500 lumens	3,800 lumens
NATIVE RESOLUTION	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	WXGA (1280x800)
MAX. COMPUTER INPUT	UXGA	UXGA	UXGA	UXGA	WUXGA
MAX. VIDEO INPUT	1080i	1080i	1080i	1080i	1080p
CONTRAST RATIO	400:1	500:1	500:1 / 1000:1	500:1	500:1
PANEL SIZE	0.63"	0.63"	0.8"	0.8"	0.74"
LENS TYPE	1.33-1.62:1	1.38-2.15:1	1.15-1.85:1	1.15-1.85:1	1.18-1.86:1
FIXED IMAGE OFFSET	Up 35.7%	Up 40%	Up 40%	Up 40%	Up 48%
KEystone CORRECTION	U/D 20°	U/D 20°	U/D 40°	U/D 40°	U/D 40°
CLOSED CAPTION	Yes	No	No	No	Yes
INPUTS	Dsub15 x 2; RCA x 1 MiniStereo x 1; RCA (audio) x 2 S-Video with included adapter	DVI-I (w/HDCP) x 1; HD15 x 1 RCA x 1; S-Video x 1 MiniStereo x 1; RCA (audio) x 2	Dsub15 x 2; RCA x 1 or S-Video x 1; MiniStereo x 1 RCA (audio) x 2	Dsub15 x 1; DVI-I (w/HDCP) x 1 RCA x 1; S-Video x 1; MiniStereo x 1 RCA (audio) x 2; Computerless SD memory card slideshow	Dsub15 x 2; HDMI (HDCP) x 1 RCA x 1; S-Video x 1; MiniStereo x 2 RCA (audio) x 2; Computerless USB memory device slideshow
OUTPUTS	Dsub15 x 1; MiniStereo x 1 (by switching inputs)	HD15 x 1; MiniStereo x 1 (by switching inputs)	Dsub15 x 1; MiniStereo x 1 (by switching inputs)	Dsub15 x 1; MiniStereo x 1 (by switching inputs)	Dsub15 x 1; MiniStereo x 1 (by switching inputs)
SOUND CONTROL	1 Watt; 1.1" dia. speaker x 1	1 Watt; 1.1" dia. speaker x 1	1 Watt; 1.1" dia. speaker x 1	1 Watt; 1.1" dia. speaker x 1	1 Watt; 1.1" dia. speaker x 1
NETWORK CONTROL	XD25U (only) Wired LAN monitoring and control	Wired/wireless LAN monitoring, control and content delivery	XB43 (only) Wired LAN monitoring and control	Wired/wireless LAN monitoring, control and content delivery	Wired/wireless LAN monitoring, control and content delivery
WARRANTY	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)
LAMP LIFE	Up to 3,500 hours	Up to 3,000 hours	Up to 3,000 hours	Up to 3,000 hours	Up to 3,000 hours
LAMP PART NUMBER	610 341 7493	610 334 9565	610 333 9740	610 333 9740	610 333 9740
FAN NOISE	As low as 30.9 dBA	As low as 29 dBA	As low as 31 dBA	As low as 31 dBA	As low as 31 dBA
AIR FILTER	Standard	Standard	Standard	Standard	Standard
MAXIMUM PITCH	± 10° U/D	Up to 360°	Up to 360°	Up to 360°	Up to 360°
WEIGHT	3.6 lb (1.6 kg)	7.5 lb (3.4 kg)	7.9 lb (3.6 kg)	8.2 lb (3.7 kg)	7.9 lb (3.6 kg)
CEILING MOUNT PN	0173-4333	0173-4312	0173-4305	0173-4305	0173-4305

EIKI INTERNATIONAL, INC.



OPTIONAL LENS PROJECTORS

DECEMBER 2009

STANDARD RESOLUTION - XGA

	CONFERENCE			AUDITORIUM	POWERHOUSE	THEATER
Note: Photos are not sized to scale.						
MODEL	LC-XG250/400	LC-XGC500	EIP-5000	LC-X80/X85	LC-X8	LC-XT5
KEY FEATURES	Cost-effective interchangeable lens projectors; Easy lens change; High-brightness; Wide range of professional inputs	Cartridge air filter; Automatic lamp changer and failsafe dependability in critical situations and hard-to-reach installations	1 DLP® imaging engine; Projector Stack and VideoWall features; Filterless design; 2 lamps	Highest brightness portables; Cartridge air filter; X85 utilizes 3LCD + one technology for superior color reproduction	Cartridge air filter; Very high brightness; 3000:1 contrast ratio; Transportable; Interchangeable input modules; 2 lamps that run on a standard 120V socket	Our brightest at 15,000 lumens; Up to 600" image diagonal; Interchangeable input modules; 4 lamps; Accepts inputs up to 1080p
DISPLAY TECHNOLOGY	3LCD	3LCD	1-chip DLP®	3LCD / 3LCD + one	3LCD	3LCD
PRICE (MSRP)	\$4,995 / \$5,995	\$6,995	\$7,495	\$9,495 / \$9,995	\$16,995	\$29,995
BRIGHTNESS (ANSI)	4,000 / 5,000 lumens	5,000 lumens	5,200 lumens	6,500 / 7,000 lumens	10,000 lumens	15,000 lumens
NATIVE RESOLUTION	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)
MAX. COMPUTER INPUT	UXGA	SXGA+	UXGA	UXGA	UXGA	UXGA
MAX. VIDEO INPUT	1080i	1080i	1080i	1080p	1080p	1080p
CONTRAST RATIO	1000:1	1100:1	1200:1	2000:1 / 2200:1	3000:1	2000:1
PANEL SIZE	1.0"	1.0"	0.7"	1.3" (inorganic)	1.8" (inorganic)	1.8" (inorganic)
LENS TYPE	1.64-2.13:1	1.6-2.1:1	1.8-2.2:1	Supplied without lens	Supplied without lens	Supplied without lens
POWER LENS SHIFT	Up 50%; L/R 15%	Up 50%; L/R 15%	Up 50%; L/R 15%	Up 50%; L/R 10%	U/D 50%; L/R 10%	U/D 50%; L/R 10%
KEystone CORRECTION	U/D 40°	U/D 40°; L/R 20°	U/D 30°; L/R 30°	U/D 35°; L/R 15°/U/D 40°; L/R 20°	U/D 40°; L/R 20°	U/D 40°; L/R 20°
INPUTS	HD15 x 1 or DVI-D (w/HDCP) x 1 BNC x 5 or BNC x 3; S-Video x 1 or RCA x 1; MiniStereo x 1 RCA (audio) x 2	Dsub15 x 1 or DVI-D (w/HDCP) x 1 BNC x 5 or BNC x 3; RCA x 1 or S-Video x 1 with RCA (audio) x 2; MiniStereo x 1	HD15 x 1; BNC x 5 or BNC x 3 DVI-D (w/HDCP) x 1; RCA x 1 S-Video x 1; MiniStereo x 1	HD15 x 1 or DVI-D (w/HDCP) x 1 BNC x 5 or BNC x 3 RCA x 3 or S-Video x 1 / X85; MiniStereo x 2	Dsub15 x 1RGB or DVI-D (w/HDCP); BNC x 5 or BNC x 3 or BNC x 1 or S-Video Empty module bay x 2	HD15 x 1, DVI-D (w/HDCP) x 1 BNC x 5; S-Video x 1 Empty module bay x 2 (Requires 240 V/60 Hz power)
OUTPUTS	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	HD15 x 1; MiniStereo x 1 (by switching inputs)	HD15 x 1; MiniStereo x 1 (by switching inputs)	—	—
SOUND CONTROL	1 Watt; 1.1" dia. speaker x 1	3 Watt; 2.0"x3.5" oval speakers x 2	3 Watt; 1.3" dia. speakers x 2	—	—	—
NETWORK CONTROL	Wired LAN monitoring and control with optional module	Wired LAN monitoring and control with optional module	Wired LAN monitoring and control	Wired LAN monitoring and control with optional module	Wired LAN monitoring and control with optional module	Wired LAN monitoring and control with optional module
WARRANTY	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)
LAMP LIFE	Up to 3,000 hours	Up to 3,000 hours per lamp	Up to 2,500 hours per lamp	Up to 3,000 hours	Up to 3,000 hours per lamp	Up to 3,000 hours per lamp
LAMP PART NUMBER	610-330-7329 / 610 335 8093	610 342 2626 (2)	AH-50001 (1) & AH-50002 (1)	610 334 2788 / 610 341 1941	610 341 9497 (2)	610 334 6267 (4)
FAN NOISE	As low as 31 / 35 dBA	As low as 32 dBA	As low as 35 dBA	As low as 31.8 / 35 Dab	As low as 45 dBA	As low as 51 dBA
AIR FILTER	Standard	Cartridge (10,000 hours)	None	Cartridge (10,000 hours)	Cartridge (10,000 hours)	Standard
MAXIMUM PITCH	Up to 360°	Up to 360°	± 9° U/D	Up to 360°	Up to 360°	± 10° U/D
WEIGHT	19.2 lb (8.7 kg) / 19.6 lb (8.9 kg)	34 lb (15.4 kg)	33.2 lb (15.1 kg)	25.8 lb (11.7 kg) / 25.1 lb (11.4 kg)	60.85 lb (27.6 kg)	80.5 lb (36.5 kg)
CEILING MOUNT PN	0173-4304	0173-4304	0173-5002	0173-4313	0173-4325	0173-4222

EIKI INTERNATIONAL, INC.

30251 Esperanza, Rancho Santa Margarita, CA 92688 Tel: 800-242-3454 E-Mail: usa@eiki.com Website: www.eiki.com

HIGH-RESOLUTION AND WIDESCREEN

	720p/WXGA (1280x800)			SXGA+ (1400x1050)		HD 1080p
Note: Photos are not sized to scale.						
MODEL	LC-WGC500	EIP-WX5000	LC-W5	LC-SXG400	EIP-SXG20	EIP-HDT20
KEY FEATURES	High-brightness widescreen (1280x800); Cartridge air filter; Automatic lamp changer and failsafe; 3000:1 contrast ratio; Picture in Picture; Picture by Picture features	High-brightness widescreen (1280x800); Advanced 3-Chip DLP® engine; Projector Stack and VideoWall features	Widescreen (1366x800); Cartridge air filter; High brightness and contrast; Interchangeable input modules	High Resolution SXGA+ (1400x1050); Push button lens changer; 4,200 lumens; Cost-effective	SXGA+ (1400x1050); Cartridge air filter (up to 35,000 hours); High brightness at 7,500 lumens; Interchangeable input modules; DICOM compatibility	1080p (1920x1080); 1DLP® image engine; interchangeable color wheels to maximize brightness or color saturation; Cartridge air filter; Interchangeable input modules
DISPLAY TECHNOLOGY	3LCD	3-chip DLP®	3LCD	3LCD	1-chip DLP®	1-chip DLP®
PRICE (MSRP)	\$7,495	\$13,995	\$14,995	\$6,995	\$14,995	\$21,995
BRIGHTNESS (ANSI)	5,000 lumens	5,200 lumens	6,000 lumens	4,200 lumens	7,500 lumens	6,500 lumens
NATIVE RESOLUTION	WXGA (1280x800)	WXGA (1280x800)	WXGA (1366x800)	SXGA+ (1400x1050)	SXGA+ (1400x1050)	1080p (1920x1080)
MAX. COMPUTER INPUT	WUXGA	WXGA	WXGA	UXGA	UXGA	WUXGA
MAX. VIDEO INPUT	1080p	1080p	1080p	1080i	1080p	1080p
CONTRAST RATIO	3000:1	1800:1	2000:1	1300:1	7500:1	7500:1
PANEL SIZE	0.95" (inorganic)	0.65"	1.22" (inorganic)	1.0"	0.95"	0.95"
LENS TYPE	1.64-2.13:1	1.8-2.5:1	Supplied without lens	1.69-2.20:1	Supplied without lens	Supplied without lens
POWER LENS SHIFT	Up 50%; L/R 15%	U/D 66%; L/R 35%	U/D 88%; L/R 13%	Up 50%; L/R 15%	U/D 55%; L/R 45%	U/D 67%; L/R 41.5%
KEystone CORRECTION	U/D 40°; L/R 20°	U/D 40°; L/R 30°	U/D 40°; L/R 20°	U/D 40°	U/D 30°; L/R 30°	U/D 30°; L/R 30°
INPUTS	HDMI (w/HDCP) x 1 or Dsub15 x 1; BNC x 5 or BNC x 3 S-Video x 1; RCA x 1 MiniStereo x 1; RCA (audio) x 2	HDMI x 1; DVI-D (w/HDCP) x 1; Dsub15 x 1 BNC x 5; S-Video x 1; RCA x 1 MiniStereo x 1	HD15 x 1RGB or DVI-D (w/HDCP) x 1; BNC x 5 or BNC x 3 or BNC x 1 or S-Video x 1 Empty module bays x 2	HD15 x 1 or DVI-D (w/HDCP) x 1 BNC x 5 or BNC x 3; S-Video x 1 RCA x 1; MiniStereo x 1 RCA (audio) x 2	Dsub15 x 1; DVI-D x 1 HDMI (w/HDCP) x 1; BNC x 5 S-Video x 1; Empty module bay x 1	HDMI (w/HDCP) x 1; DVI-D x 1; Dsub15 x 1; BNC x 5; S-Video x 1
OUTPUTS	Dsub15 x 1 MiniStereo x 1	Dsub15 x 1 MiniStereo x 1	—	HD15 x 1 MiniStereo x 1	Dsub15 x 1	Dsub15 x 1
SOUND CONTROL	3 Watt; 2.0" x3.5" oval speakers x 2	3 Watt; 1.3" x2.6" oval speakers x 2	—	1 Watt; 1.1" dia. speaker x 1	—	—
NETWORK CONTROL	Wired LAN monitoring and control with optional module	Wired LAN monitoring and control	Wired LAN monitoring and control with optional module	Wired LAN monitoring and control with optional module	Wired LAN monitoring and control	Wired LAN monitoring and control
WARRANTY	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)	3 years ownership or 6,000 hours use, (whichever occurs first)
LAMP LIFE	Up to 3,000 hours per lamp	Up to 3,000 hours per lamp	Up to 3,000 hours per lamp	Up to 3,000 hours	Up to 2,500 hours per lamp	Up to 2,500 hours per lamp
LAMP PART NUMBER	610 342 2626 (2)	AH-55001 (2)	610 337 0262 (2)	610 335 8093	610 343 5336 (2)	610 343 5336 (2)
FAN NOISE	As low as 31 dBA	As low as 34 dBA	As low as 50 dBA	As low as 35 dBA	As low as 36 dBA	As low as 36 dBA
AIR FILTER	Cartridge (10,000 hours)	Standard	Cartridge (10,000 hours)	Standard	Cartridge (up to 35,000 hours)	Cartridge (up to 35,000 hours)
MAXIMUM PITCH	Up to 360°	± 9° U/D	Up to 360°	Up to 360°	Up to 360°	Up to 360°
WEIGHT	34 lb (15.4 kg)	58.4 lb (26.5 kg)	60.85 lb (27.6 kg)	19.62 lb (8.9 kg)	44.1 lb (20 kg)	44.1 lb (20 kg)
CEILING MOUNT PN	0173-4304	0173-5015	0173-4325	0173-4304	0173-5016	0173-5016

EIKI INTERNATIONAL, INC.

30251 Esperanza, Rancho Santa Margarita, CA 92688 Tel: 800-242-3454 E-Mail: usa@eiki.com Website: www.eiki.com